

PERSONAL PROTECTIVE EQUIPMENT:

Safety glasses with side shields are recommended to keep dust out of the eyes. Use ear protection (earplugs, hood, or earmuffs) to prevent airborne dust or fibers from entering the ear, if necessary. Leather or cotton gloves should be worn to protect against mechanical abrasion. Optional: wear a NIOSH-certified disposable or reusable particulate respirator with efficiency rating of N95 or higher (per 42 CFR 84) except required when dust or fiber concentrations exceed the applicable exposure limits of dust 15 mg/m³. Wear a cap, a loose-fitting, long-sleeved shirt and long pants to protect skin from irritation. Exposed skin areas should be washed with soap and water after handling or working with fiberglass.

SITE PREPARATION AND INSTALLATION REQUIREMENTS:

Other trades, including but not limited to, electrical, plumbing, and mechanical should have already installed their required materials prior to loose-fill blown-in fiberglass being installed. Proper air sealing should be complete prior to loose-fill fiberglass installation to insure full performance of the thermal insulation. Verify all holes and seams between drywall ceiling and any penetrations through the ceiling are sealed with durable caulk, tape, and/or foam sealants. Johns Manville blown-in fiberglass is easy to install with the instructions below and there is no certification program for this material. Although Johns Manville supports individuals who choose to hire one of the many experienced installation professionals that use our products every day, inexperienced installers can also use our blown-in fiberglass, provided they follow the instructions contained in this document. The area during and after installation of fiberglass batts may be used by other trades or occupants. There are no time restrictions for re-entry into the area.



ENERGY AND ENVIRONMENT






Installed blowing wool

INSULATING CEILINGS / ATTIC FLOORS:

In addition to making your home more comfortable and energy-efficient, insulating your attic floor / ceiling provides essential sound control between floors in your home. Properly insulating the ceilings will make your home a more peaceful and quiet place because it will ensure that footsteps and other sounds do not migrate to other rooms.

HOW TO INSTALL BLOWN-IN INSULATION:



1. Remove any objects from the attic that might interfere with the proper application of the insulation.
2. Make sure that any eave or soffit vents are not blocked. Verify 1" ventilation baffles/vent chutes are installed at eave vents and they extend above the new level of insulation.
3. Verify can lights are IC rated. IC rated can lights may have insulation in contact; non-IC rated can lights must have shields to maintain/block 3" clearance around the fixture, electrical box, and ballast. See section on "Special Considerations, Critical Details & Tips."
4. Barriers of batt insulation will be installed to prevent loose-fill insulation from falling into soffits, scuttle entrance, damming for unconditioned spaces (porches or garages), or from contacting hot surfaces. Unfaced batts are the preferred blocking material. Metal flashing and fire-rated caulk are the preferred materials for protecting hot surfaces.
5. Verify attic floor is air sealed from the living space below. Seal all shafts for pipe, duct and the flue penetrations using fire-rated caulk when required. Seal sheetrock to top plate seam at all attic/ wall surfaces. Seal all wire penetrations through the top plate. Seal around all ceiling openings for surface lighting, ceiling fans, bathroom fans, etc., seal air barriers above all open soffits and dropped/coved ceilings. Ensure that the attic hatch or drop-down stair opening is sealed with weather stripping and seal the dry wall to can light connection for all recess lighting using fire-rated caulk when required.
6. Place one or more attic rulers in each quadrant of the attic space. This will help you know when you have achieved the correct depth of insulation.
7. Load the blowing machine hopper with insulation. The hopper should be kept nearly full so the insulation flow is smooth and even.
8. Hold the hose parallel to the floor with the insulation falling 10' - 12' away. Begin at the far wall and work toward the center. Always blow in the direction of the joists. Be careful to step only on floor joists, or else you might accidentally put your foot through the finished ceiling below.
9. Fill three or four joist cavities by moving the hose to the right and left. Where possible back away from the work to avoid packing the insulation. Be sure to get insulation to the top of the walls and low places. Don't cover eave vents.
10. Avoid using your hand as a baffle to direct the insulation as it exits the hose. Do this only when necessary to avoid packing.
11. Keep the hose close to the floor where insulation must go under obstructions like cross bracing and wiring. Insulation must be blown on both sides of these kinds of obstructions. If an obstruction has caused a low spot to occur, fill in the area.
12. Check the thickness of the insulation, and check that you have used the correct number of bags per 1,000 sq. ft.

INSULATING AROUND RECESSED LIGHTS IN CEILINGS:

Recessed lighting fixtures, as well as fan motors and other heat sources protruding into the ceiling, are a potential fire hazard. Building and fire codes require that there be at least a 3" clearance from any heat-generating source—including chimneys—unless the fixture is IC rated. This rating will be clearly marked on the fixture.

To ensure that this 3" clearance is maintained, you can install a baffle made with metal, cardboard or sheet metal around the heat source. If there are facing materials, trim them around the baffle to ensure adequate clearance from the fixture.

Special Considerations, Critical Details & Tips

INSULATING SCUTTLES & PULL-DOWN STAIRWAYS:

A scuttle is the opening for accessing the attic. Scuttles, pull-down stairways and other attic access holes should also be insulated to the same R-value as your attic.

Many attics are filled with loose-fill insulation. However, that does not work for scuttles or pull-down stairways. Batt insulation, however, can be glued directly to a scuttle hatch. Pull-down stairways may require a build-up framework to lay batts on and around.

If you have pull-down attic stairs or an attic door, seal these similarly: Weatherstrip the edges and put a piece of rigid foam board insulation on the back of the door.

RECOMMENDED EQUIPMENT:

For smaller, DIY projects, see your retailer for machine rental and use. Small blowing machines typically consist of a base and a hopper; 50' power cord with twist/lock end; two sections of 50' 2-1/2" blowing hose with quick-connect coupler set attached; and wireless remote attached to the end of the hose. Professionals often use larger machines which can process bigger volumes of material and have longer, larger diameter hoses.

FOR COVERAGE INFORMATION BASED ON R-VALUE, PLEASE REFER TO THE PRODUCT PACKAGING OR VISIT THE BUILDING INSULATION PAGE ON JM.COM.