

Features and Components

Use: JM Coating Repair Tape is used to seal seams, flashings and repair areas of existing roof prior to application of JM Coating Membrane systems.

Materials: A high-strength sealing tape with a polyester stitch-bonded fleece top surface.

Colors: White fleece top



Component

L
Liquid

A
Accessory

Type

FL
Flashing

Multi-Ply
Single Ply

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP*		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
<i>For use with the selected multi-ply systems above</i>									

Single Ply	TPO				PVC**			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
<i>For use with the selected single ply systems above</i>										

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

*APP cap sheet only

**Not compatible with JM PVC SD Plus

Physical Properties

Property	JM Coating Repair Tape
Peel Strength	21 lbs. +/-in width
Elongation	750%
Low Temperature Flexibility (-65°F)	no cracking
Permeability	.001 perms max
Tensile Break	800+/-50 psi (5.5 ± 0.34 Mpa)
Total Thickness	35 mils

Installation/Application



Self-Adhered

- Refer to JM Coating applicator guides and detail drawings for instructions.
- Please refer to JM Coatings Application Guide.

Packaging and Dimensions

Roll Width	4" (10.2 cm)	6" (15.2 cm)
Roll Length	50' (15.2 m)	50' (15.2 m)
Coverage	16.7 ft ² (1.6 m ²)	25 ft ² (2.3 m ²)
Rolls/Box	12	8
Linear ft/box	600 (182.9 m)	400 (121.9 m)

Storage

Shelf Life	2 years from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, in original unopened containers
Temperature Range	40°F – 85°F (4°C – 29°C)