






Product	Use	Description	Application Method	Size	Standard
SeamFree™ Liquid Membrane	Cap or Flashing	A two-component, elastomeric liquid-applied waterproofing product consisting of an asphalt/urethane base material and an activator.		Base – 4.4 gal (16.7 l) pails Activator – 44.1 fl oz (1.3 l) bottles	
SeamFree™ Scrim	Scrim	A stitchbonded polyester scrim.		40" x 324' (102 cm x 98.76 m)	
PermaFlash® Primer	Flashing Primer	Organo-silane compound dispersed in isopropyl alcohol. It improves adhesion of MBR® Flashing Cement to nonporous surfaces such as metals and some plastics. PermaFlash Primer is part of the PermaFlash integrated flashing system.		(6) 16 oz (473 ml) bottles/case	None
PermaFlash® Scrim	Flashing Scrim	Stitchbonded polyester scrim that offers a sturdy combination of burst strength and toughness. PermaFlash Scrim is part of the PermaFlash integrated flashing system.		12" (305 mm) wide 100 yds (91.4 m) long	None
MBR® Flashing Cement	Flashing Cement	A two-part, urethane-based, trowelling grade, elastomeric adhesive for use with SBS modified bitumen and BUR flashing for use with the PermaFlash® Bituminous Flashing System.		Approx. 4½ gal (17.0 l) can	None