

1. How many rolls of tape come in a carton?

16 rolls.

2. Can I break a master carton, for example if I need 3 rolls, can I get only 3 rolls?

No, we will not break cartons. The tape must be purchased in full box quantities of 16 rolls.

3. Does JM offer 96mm wide tape?

No, not at this time.

4. How should I apply the tape?

The best way to apply the tape is with a plastic squeegee. Using a metal edge, like the back of a duct knife or a metal squeegee, may be too abrasive.

5. Can I pull the tape off and reset it on the surface?

Every attempt should be made to not remove or replace the tape once it has been adhered to the facing. If you adhere the tape and then pull the tape off, it may also pull off some of the facing on the Spin-Glas board itself.

6. Do any other tapes provide an exact match to 800 Series Spin-Glas Ultra?

No, this is the only tape that provides an exact match. While other polypropylene coated ASJ tapes are similar, there is a paper layer in their facing composition that creates a visual difference. The facing in the 800 Series Spin-Glas Ultra boards and tape have no paper layer.

7. Can Spin-Glas Ultra tape be used on Micro-Lok HP Ultra pipe insulation?

We do not recommend using Spin-Glas Ultra tape on Micro-Lok HP Ultra pipe insulation. While both Micro-Lok HP Ultra and 800 Series Spin-Glas Ultra have a facing with a polypropylene coating, the facing on 800 Series Spin-Glas Ultra and Spin-Glas Ultra tape is unique in that there is no paper layer. This does create a slight visual difference to Micro-Lok HP Ultra. While 800 Series Spin-Glas Ultra can be installed next to Micro-Lok HP Ultra for a close match, we do not recommend using Spin-Glas Ultra tape on Micro-Lok HP Ultra. Micro-Lok HP Ultra butt strips should be used instead.

8. Does the Spin-Glas Ultra tape meet ASTM E84 25/50 standards?

Yes, the Spin-Glas Ultra tape meets the ASTM E84 25/50 surface burning characteristics of building materials, the same as Spin-Glas Ultra boards.



717 17th St.
Denver, CO 80202
800-654-3103
www.JM.com

**North American Sales Offices,
Insulation Systems**

Eastern Region and Canada

P.O. Box 158
Defiance, OH 43512
800-334-2399
Fax: 419-784-7866

Western Region

P.O. Box 5108
Denver, CO 80217
800-368-4431
Fax: 303-978-4661

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The physical and chemical properties of 800 Series Spin-Glas Ultra Tape listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Any references to numerical flame spread or smoke developed ratings are not intended to reflect hazards presented by these or any other materials under actual fire conditions.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville thermal insulation and systems, visit www.jm.com/terms-conditions or call (800)654-3103.